

Controls for the remote operation of climate controllers PFB

For surface installation – Design Pikolo









Technische Daten

Operating voltage:	24 V ~ ... 250 V ~ /50/60 Hz +10/-15% at 24 V ~ min. 100 mA
Switching current:	6 (3) A (PFB 20)/2 (2) A (PFB 02)
Switch:	see below – max. 2 switches possible
Degree of protection:	IP 30
Protection class:	II, after acc. installation
Admissible air moisture:	max. 95 % r.h., non condensing
Storage temperature:	-20 ... +70 °C
Ambient temperature:	-10 ... +40 °C
Housing colour:	pure white, similar to RAL 9010
Housing material:	plastic (ABS)
Mounting/installation:	surface installation/wall mounting
Weight:	approx. 75 g
Electrical connections:	terminal screws

Application

Control for the remote operation of air conditioning systems (e.g. fancoils).

Model/Picture	Item No.	Equipment		Circuit diagram	PG
	A 201213	1 st switch: ON/OFF 2 nd switch: for fan operation at three different speed stages "slow/medium/fast"	TYP PFB02 $\frac{2(2)A}{250V} \sim$ CE		A
	A 201232	1 st switch: ON/OFF 2 nd switch: for fan operation at three different speed stages "slow/medium/fast"	PFB20.801 $\frac{250 V \sim}{6 (3) A}$ T30 4K/h CE		A
	A 201233	1 st switch: "heating/off/cooling" 2 nd switch: for fan operation at three different speed stages "slow/medium/fast"	PFB20.802 $\frac{250 V \sim}{6 (3) A}$ T30 4K/h CE		A

Flush mounted remote controls available on request – see also FUF as of page 125.

